


ITEM	DESCRIPTION	PART NUMBER	QTY
1	BOLT ON HANGER - LH	W1627-1	1
2	BOLT ON HANGER - RH	W1627-2	1
3	BEAM W/ BUSHING FOR I-BEAM AXLE	AW1628	2
4	PIVOT BOLT KIT 7/8"-9 UNC X 7" LONG	K0928	2
4a	HHCS, 7/8"-9 UNC X 7" LONG, GRADE 8, YELLOW ZINC	H0126	1
4b	4" CAM GEAR WASHER	F0832	2
4c	WEAR WASHER, 3.13" ID X 6.5" OD - UHMW	C0406	1
4d	SHEAR-TITE™ NUT, 7/8"-9 UNC	H1120	1
5	LIFT BAG (64552 CONTI) (2B9-251 GOODYEAR)	C0080-CONTI	2
6	LOAD BAG, TRIPLE CONVOLUTE (161355 CONTI)	C0112-CONTI	2
7	AIR SPRING MOUNTING KIT	K0929	2
7a	HHCS, FLANGELOCK 3/8"-16UNC X 1" LONG	H0401	4
7b	SET SCREW, 3/8"-16 UNC X 3/4" LONG	H0400	1
7c	L'NUT, NYLOCK, 3/4"-16 UNF, GRADE 2 OR GR 5, SILVER ZINC	H1202	1
7d	L'NUT, SERRATED HEAD, 1/2"-13UNC ZINC PLATED	H1301	2
8	AIR LINE BRACKET	F1724	2

**APPLICATION NOTE:**  
 THIS SUSPENSION IS FOR LOCKED STEERING AXLE ONLY. IF THE STEERING AXLE IS USED, IT IS THE RESPONSIBILITY OF THE CUSTOMER TO ACCOUNT FOR 3 TO 5 DEGREE CASTER ANGLE AT THE AXLE DOWN RIDE HEIGHT AND THAT A STEERING DAMPNER KIT IS USED.

DCN#	REV	REVISION DESCRIPTION	DATE	BY	CHK	APP	
DRAFTSMAN: DWalk	07/2017	TITLE:					
CHECKED: CHK		CUSH AUXILLARY I-BEAM AXLE					
RELEASED: APP		13K SUSP WEIGHT RATING					
WEIGHT: N/A		9-11" RIDE HEIGHT					
MATERIAL:		BOLT-ON RAIL HANGER					
All of the Information shown herein is the intellectual property of Cush Corp and is submitted only on a confidential basis. The recipient agrees that no disclosure of this information will be made to a third party without written consent of Cush Corp.		TOLERANCE UNLESS OTHERWISE STATED: XX = +/- .002 FRACTIONS = +/- .1116 XXX = +/- .001 ANGLES = +/- .1°		Nixa, MO, USA PHONE: 417-724-1239 www.cushcorp.com			
PROJECT NO:	17046	SHEET OF:	3 OF 6	SCALE:	A-SIZE: NTS B-SIZE: 1/X D-SIZE: 1/4		DRAWING(PART) NO: